

A VUBA
INNOVATION



EASIHOLD
POWERED BY ECCO

Water-permeable, user-friendly water-based binder.

Easihold powered by ECCO is a water-permeable binder that holds loose gravel and bark in place. It is completely free of microplastics, non-toxic, and provides immediate adhesion thanks to Dual Bond Technology.

Gravel that doesn't budge an inch. A garden path without loose stones, a border without bark blowing away. Easihold powered by ECCO is a water-permeable, water-based binder that keeps loose stones and bark in place. For a solid, water-permeable surface that keeps looking neat.

Technical specifications

Application temperature	5°C – 45°C
Curing time	12–36 hours (depending on humidity and temperature)
UV-resistant	Yes
Shelf life	24 months unopened; 12 months after opening (reseal and store between 5°C and 45°C)
Suitable aggregate sizes	4–7 mm; 8–18 mm; 19–25 mm (Not suitable for porous or white stones)
Packaging	4,1 l; 2 l, 800 ml
Max. gravel layer thickness	2,5 cm

Benefits



100%
water-permeable



Fast installation



Dual Bond
Technology:
immediate
bonding



Free from
microplastics



Bio-based
certification



Non-toxic and
non-hazardous
ingredients
(VOCfree)

Coverage



800 ml

2 m²



2 l

5 m²



4 l

10 m²

Installation

01 Preparation

- Measure the area to determine the total surface to be treated.
- Check the weather forecast and ensure no rain is expected within the next 24 hours and that the temperature remains above 5°C.
- Only use washed and dried gravel.
- **Make sure the stones are clean, free from dust and dirt, and completely dry, including the underlying layer.**
- Protect surrounding areas to prevent spills.
- Apply Easihold only to materials installed on a water-permeable base.
- Use a clean, new airless sprayer filled with Easihold.
- Wear gloves.

02 Application: spray method

- Shake the container well and pour Easihold into the sprayer. The use of an airless sprayer is recommended.
- Apply the first coat to the clean, dry surface. Spray evenly according to the recommended coverage guidelines and ensure all stones are well coated.
- Lightly compact the surface with a flat tool by gently pressing down.
- Wait 30 minutes to 1 hour, then apply the second coat.
- Compaction is no longer necessary. Allow the surface to cure undisturbed for 36 hours.
- Always close the spray nozzle of the 800 ml bottle tightly to prevent clogging.

03 Application: mixing method

- Pour Easihold into a bucket together with the stones and mix until all stones are evenly coated.
- Pour the mixture onto the surface and spread to a layer thickness of approx. 20 mm.
- Compact the stones with a trowel and then allow to dry for 36 hours.



Aftercare

- Avoid load or pressure on the surface during the first 24 hours after the final coat.
- If it rains during the drying process, reapplication may be necessary.
- In high-traffic pedestrian areas: reapply every 12 months.
- For decorative use: reapply every 24 months.
- Remove loose stones to prevent further wear.
- Any missed or loose areas can be repaired locally with two coats of Easihold and light compaction