



# ECCOsedum

## The ready-to-use green roof tiles.

Can be placed on a flat roof as well as on an inclined roof.



### INFO

- + Easy to handle: installation of the green roof is very simple
- + Low weight per m<sup>2</sup>: maximum 84 kg in fully saturated condition
- + The ECCOsedum system can therefore be applied to almost any existing roof
- + Placement is possible all year round
- + Easily removable if needed for roof work
- + Constant substrate thickness
- + Nicely flattened pressure points on the side of the tile, resulting in an even better pressure distribution
- + Buffer volume of the system is at least 35 litres/m<sup>2</sup> (trays + protective layer)

### TECHNICAL SPECIFICATIONS

- |   |  |
|---|--|
| + COMPOSITION - 100% PP - Polypropylene   | + NUMBER OF TILES PER M <sup>2</sup> - 4.4 pieces            |
| + DIMENSIONS - 49.5 cm x 45.5 cm x 8 cm   | + STORAGE CAPACITY WATER - 32.5 litres/m <sup>2</sup>        |
| + WEIGHT DRY - 11.7 kg/cassette - 51.5 kg/m <sup>2</sup> *  | + APPLICATION - flat and slightly inclined roofs (up to 25°) |
| + WEIGHT SATURATED - Max. 19 kg/cassette - 84 kg/m <sup>2</sup> *   | + BUILDING LAYERS - drainage, substrate and vegetation layer |
| + ** These are theoretical values. In practice, they may vary slightly because the tiles may expand when filled with substrate. |  |

- + Subscribe to the ECCOPRODUCTS YouTube channel for product, assets- and installation videos
- + If you want to receive all the latest information and news on our product range, like or follow our other social media channels.

