



2Connect

Weed-free joint filler for heavy traffic loads
epoxy-based




INFO

- + Prevents weed growth in (paving) joints
- + Water- and air-permeable
- + Suitable for applications with heavy traffic
- + Application possible in wet and dry weather
- + Applicable to both new and existing paving
- + Durable and maintenance-friendly
- + UV- and frost-resistant
- + Eco-friendly solution


FARBEN



NEUTRAL



STONE GREY



BASALT

SPECIFICATIONS

- + COMPOSITION: Comp. A (epoxy resin) + Comp. B (hardener)
- + COMPRESSIVE STRENGTH : min. 21 N/mm²
- + TENSILE STRENGTH: 6,1 N/mm²
- + JOINT WIDTH/DEPTH: min. 6 mm, min. 50 mm
- + DRYING TIME: 24h - 48h

APPLICATIONS

Suitable for pavements with heavy loads:

- + Roundabouts
- + Cobblestone roads
- + Roads with wide joints

Min. outdoor temperature at installation: > 5°C and < 30°C

- + Subscribe to the ECCOPRODUCTS YouTube channel for product- and installation videos
- + Want to receive all the latest information and news on our product range, like or follow our other social media channels.

ECCO  **PRODUCTS**



ECCO bvba - Poelstraat 167, BE-9820 Merelbeke



+32 9 247 00 25



www.eccoproducts.eu