



2Connect

Weed-free joint filler for heavy traffic loads
epoxy-based




INFO

- + Prevents **weed growth** in (paving) joints
- + **Water- and air-permeable**
- + Suitable for applications with **heavy traffic**
- + Application possible in wet and dry weather
- + Applicable to **both new and existing paving**
- + Durable and maintenance-friendly
- + UV- and frost-resistant
- + Eco-friendly solution

COLOURS



NEUTRAL



STONE GREY



BASALT

SPECIFICATIONS

- + COMPOSITION: Comp. A (epoxy resin) + Comp. B (hardener)
- + COMPRESSIVE STRENGTH : min. 21 N/mm²
- + TENSILE STRENGTH: 6,1 N/mm²
- + JOINT WIDTH/DEPTH: joints from 5 mm wide and 3 cm deep
- + DRYING TIME: 24h - 48h

APPLICATIONS

- Suitable for pavements with heavy loads:
- + Roundabouts
 - + Cobblestone roads
 - + Roads with wide joints

Min. outdoor temperature at installation: > 5°C and < 30°C

Less suitable for ceramic tiles, bluestone and porous materials.

- + Subscribe to the ECCOPRODUCTS YouTube channel for product- and installation videos
- + Want to receive all the latest information and news on our product range, like or follow our other social media channels.

ECCO  **PRODUCTS**